

# 89-0FM-PMC-070-002

## 7.0" Open Frame Touch Monitor



### STANDARD CONFIGURATION

- Industrial-Grade LCD
- Multi-Touch Capacitive Sensor (G/G)
- Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Steel Housing
- Rear VESA Mounts
- Optional Adjustable Flange Side-Mounts
- USB Plug-And-Play Windows 7+
- Power, Video, Touch Communication Cables Included

### CUSTOMIZABLE FEATURES

- Sunlight Readable / Superbright / NVIS
- Android / Windows Integration
- Custom Cover Glass and Graphics
- Water Resistant Multi-touch
- Gloved Touch
- Ruggedization

DISPLAY	
Size	7.0"
Pixel Pitch	0.1905 mm x 0.1905 mm
Resolution	800 x 480
Viewing Angle	160° H / 160° V
Brightness	600 nits
Support Color	16.2 million
Response Time	25 ms
Contrast Ratio	1500 : 1
Aspect Ratio	16 : 9
TOUCH SCREEN	
Technology	Projected Capacitive Multi-touch
Response Time	5 ms
SYSTEM	
Connectivity	HDMI, VGA, DVI
OPERATING ENVIRONMENT	
Temperature	-20° to 70° C
PHYSICAL	
Enclosure Type	Open Frame
Mounting Options	Rear VESA, Optional Side Flanges
Frame Type	Powder-coated Aluminum
Weight	-- lbs
WARRANTY	1 yr Parts & Labor

### APPLICATIONS

- Aerospace
- Medical
- Industrial
- Transportation
- Retail & Public Use

