

OFX

OPEN FRAME TOUCH



89-OFM-PMC-121-003

STANDARD CONFIGURATION

- Industrial-Grade LCD
- Multi-Touch Capacitive Sensor (G/G)
- Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Steel Housing
- Rear VESA Mounts
- Optional Adjustable Flange Side-Mounts
- USB Plug-And-Play Windows 7+
- Power, Video, Touch Communication Cables Included

CUSTOMIZABLE FEATURES

- Sunlight Readable / Superbright / NVIS
- Android / Windows Integration
- Custom Cover Glass and Graphics
- Water Resistant Multi-touch
- Gloved Touch
- Ruggedization

SPECIFICATIONS

DISPLAY

Size	12.1"
Pixel Pitch	0.204 mm x 0.204 mm
Resolution	1280 x 800
Viewing Angle	178° H / 178° V
Brightness	500 nits
Support Color	16.7 million
Response Time	25 ms
Contrast Ratio	1000 : 1
Aspect Ratio	16 : 10

TOUCH SCREEN

Technology	Projected Capacitive Multi-touch
Response Time	5 ms

SYSTEM

Connectivity	HDMI, VGA, DVI
--------------	----------------

OPERATING ENVIRONMENT

Temperature	-30° to 85° C
-------------	---------------

PHYSICAL

Enclosure Type	Open Frame
Mounting Options	Rear VESA, Optional Side Flanges
Frame Type	Powder-coated Aluminum
Weight	3.5 lbs

WARRANTY	1 yr Parts & Labor
----------	--------------------

APPLICATIONS

- Aerospace
- Medical
- Industrial
- Transportation
- Retail & Public Use



