

# OFX

OPEN FRAME TOUCH



## 89-OFM-PMC-70-002

### STANDARD CONFIGURATION

- Industrial-Grade LCD
- Multi-Touch Capacitive Sensor (G/G)
- Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Steel Housing
- Rear VESA Mounts
- Optional Adjustable Flange Side-Mounts
- USB Plug-And-Play Windows 7+
- Power, Video, Touch Communication Cables Included

### CUSTOMIZABLE FEATURES

- Sunlight Readable / Superbright / NVIS
- Android / Windows Integration
- Custom Cover Glass and Graphics
- Water Resistant Multi-touch
- Gloved Touch
- Ruggedization

## SPECIFICATIONS

### DISPLAY

Size	7.0"
Pixel Pitch	0.1905 mm x 0.1905 mm
Resolution	800 X 480
Viewing Angle	160° H / 160° V
Brightness	600 nits
Support Color	16.2 million
Response Time	35 ms
Contrast Ratio	1500 : 1
Aspect Ratio	15 : 9

### TOUCH SCREEN

Technology	Projected Capacitive Multi-touch
Response Time	5 ms

### SYSTEM

Connectivity	HDMI, VGA, DVI
--------------	----------------

### OPERATING ENVIRONMENT

Temperature	-20° to 70° C
-------------	---------------

### PHYSICAL

Enclosure Type	Open Frame
Mounting Options	Rear VESA, Optional Side Flanges
Frame Type	Powder-coated Aluminum
Weight	1.4 lbs

WARRANTY	1 yr Parts & Labor
----------	--------------------

### APPLICATIONS

- Aerospace
- Medical
- Industrial
- Transportation
- Retail & Public Use



