

# OFX

SUNLIGHT READABLE

## SPECIFICATIONS



### 89-OFM-SR-101-002

#### STANDARD CONFIGURATION

- Industrial-Grade LCD
- Anti-glare
- Multi-Touch Capacitive Sensor
- Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Aluminum Housing
- Rear VESA & Optional Side Brackets
- USB Plug-And-Play Windows 7+
- Power, Video, Touch Communication Cables Included

#### CUSTOMIZABLE FEATURES

- Night Vision (NVIS)
- Android / Windows Integration
- Custom Cover Glass and Graphics
- Water Resistant Multi-touch
- Gloved Touch
- Ruggedization

DISPLAY	
Size	10.1"
Pixel Pitch	0.0565 mm x 0.0565 mm
Resolution	1280 x 800
Viewing Angle	170° H / 170° V
Brightness	1000 nits [+/- 5%]
Color Support	16.7 million
Response Time	15 ms
Contrast Ratio	800 : 1
Aspect Ratio	16 : 10
TOUCH SCREEN	
Technology	Projected Capacitive Multi-touch
Response Time	< 10 ms
SYSTEM	
Connectivity	HDMI, VGA, DVI
OPERATING ENVIRONMENT	
Temperature	-20° to 70° C
PHYSICAL	
Enclosure Type	Open Frame
Mounting Options	Rear VESA, Optional Side Brackets
Frame Type	Powder-coated Aluminum
Weight	3.5 lbs
WARRANTY	1 yr Parts & Labor

#### APPLICATIONS

- Aerospace
- Medical
- Industrial
- Transportation
- Retail & Public Use

