

OFX

OPEN FRAME TOUCH



89-OFM-STD-121-002

STANDARD CONFIGURATION

- Industrial-Grade LCD
- Multi-Touch Capacitive Sensor
- Optically Bonded
- HDMI/DVI/VGA Input
- Powder Coated Aluminum Housing
- Rear VESA Mounts
- Optional Side Brackets
- USB Plug-And-Play Windows 7+
- Power, Video, Touch Communication Cables Included

CUSTOMIZABLE FEATURES

- Sunlight Readable / Night Vision (NVIS)
- Android / Windows Integration
- Custom Cover Glass and Graphics
- Water Resistant Multi-touch
- Gloved Touch
- Ruggedization

SPECIFICATIONS

DISPLAY

Size	12.1"
Pixel Pitch	0.24 mm x 0.24 mm
Resolution	1024 x 768
Viewing Angle	160° H / 160° V
Brightness	500 nits
Color Support	16.2 million
Response Time	35 ms
Contrast Ratio	700 : 1
Aspect Ratio	4 : 3

TOUCH SCREEN

Technology	Projected Capacitive Multi-touch
Response Time	< 10 ms

SYSTEM

Connectivity	HDMI, VGA, DVI
--------------	----------------

OPERATING ENVIRONMENT

Temperature	-30° to 85° C
-------------	---------------

PHYSICAL

Enclosure Type	Open Frame
Mounting Options	Rear VESA, Optional Side Brackets
Frame Type	Powder-coated Aluminum
Weight	3.6 lbs

WARRANTY	1 yr Parts & Labor
----------	--------------------

APPLICATIONS

- Aerospace
- Medical
- Industrial
- Transportation
- Retail & Public Use

